

SCREEN U.S.A.®

TRACK CONVEYORS



TRACK MOUNTED CONVEYORS

TC6036

- 36" width belt • 60' length

TC5036

- 36" width belt • 50' length



SCREEN USA, INC.

**1772 CORN RD
SMYRNA, GA 30080**

**770-433-2440
SCREENUSA.NET**

SCREEN U.S.A.®

TC6036 (36" x 60')

ENGINE

- 50HP Deutz 2.2 Tier 4 Final Diesel

FRAME

- Deep folded plate frame constructed with heavy duty cross bracing for strength and stability
- Hydraulic folding head section

IDLERS

- 35 degree CEMA B standard idlers
- Impact bed at feedpoint

UNDERCARRIAGE

- 8' tracks with 16" shoes
- Umbilical cord remote control
- Hydraulic raise and lower
- Galvanized trestle with variable feed and discharge heights

FEEDBOOT

- Drilled for liners
- 5-1/2' long with adjustable rubber skirting

BELT

- 3-ply vulcanized
- Chevron belt (Optional)
- Self adjusting polyurethane belt cleaner

OTHER

- Mesh under conveyor guarding to 5-1/2' from ground
- Side skirting 5-1/2' from ground
- All nip points guarded
- Remote greasing to all bearing from ground level
- Can ship in a 40' container
- Max stockpiling height of 26' (at 26 degrees)
- Max stockpiling capacity of 745 cu.yd.

TC5036 (36" x 50')

ENGINE

- 24HP Perkins 403J Tier 4 Final diesel

FRAME

- Deep folded plate frame constructed with heavy duty cross bracing for strength and stability
- Hydraulic folding head section

IDLERS

- 35 degree CEMA B standard idlers
- Impact bed at feedpoint

UNDERCARRIAGE

- 8' tracks with 16" shoes
- Umbilical cord remote control
- Hydraulic raise and lower
- Galvanized trestle with variable feed and discharge heights

FEEDBOOT

- Drilled for liners
- 5-1/2' long with adjustable rubber skirting

BELT

- 3-ply vulcanized
- Chevron belt (Optional)
- Self adjusting polyurethane belt cleaner

OTHER

- Mesh under conveyor guarding to 5-1/2' from ground
- Side skirting 5-1/2' from ground
- All nip points guarded
- Remote greasing to all bearing from ground level
- Can ship in a 40' container
- Max stockpiling height of 22' (at 26 degrees)
- Max stockpiling capacity of 620 cu.yd.

